

Portaflow PT400 Portable Transit Time Flow Meter

Approximate shipping weight: 13 lbs / 6 kg

Model	PT400 -
-------	---------

STANDARD FEATURES:

- Transducers - Pair of Type 'A' for 0.5" to 4.5" (13-115 mm) diameter pipes
- Transducer cables - 6 ft (2 m) coaxial pair with connectors
- Transducer mounting kit with guiderail, stainless hardware and ultrasonic couplant
- enclosure - IP54, ABS
- carrying case - IP54, plastic
- display - 240 x 64 pixel backlit LCD with graphics capability, volumetric flow, velocity, total, operating menu, battery & signal level
- calibration - built-in 16-key menu system
- outputs - 0/4-20mA (620 ohms)
- 5V open collector pulse
- power input - built-in NiMH battery rated for up to 20 hrs operation
- external charger 100-240VAC 50/60Hz
- 1 Manual - Installation and Operation

TRANSDUCERS (A and B Transducers are **not** interchangeable)

Standard - Type 'A' for 0.5" to 4.5" (13-115 mm) diameter pipes	A
Type 'B' for 2" to 40" (50-1000 mm) diameter pipes	B

OPTIONS AND ACCESSORIES

QTY	CODE	DESCRIPTION	PRICE
	PT-A	Replacement Transducer pair Type A for 0.5" to 4.5" (13-115 mm) diameter pipes - for 'A' configured PT400 only	\$695.00
	PT-B	Replacement Transducer pair Type B for 2" to 40" (50-1000 mm) diameter pipes - for 'B' configured PT400 only	\$795.00
	PTSC1	Replacement Transducer Cable pair, 6 ft. (2 m) with locking connectors	\$165.00
	PTSC2	Replacement Transducer Cable pair, 32 ft. (10 m) with locking connectors	\$230.00
	PTG1	Replacement pair Guiderails with Chains and Ruler	\$495.00
	PTCN	Replacement Guiderail Chains	\$8.00
	PTRE	Replacement Guiderail Ruler, engraved – Metric and Imperial	\$95.00
	PTIP54	Replacement Carrying Case, IP54 plastic, with foam insert	\$225.00
	CC-SL30	Coupling Compound – Super Lube® 3.0 oz tube	\$38.00
	MNL	Additional Manual (One supplied with each unit)	\$10.00